



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE COLOR POSITIONS MAY VARY.
6. VOIDS LARGER THAN  $\phi$  .035 [.89] ARE NOT ACCEPTABLE.
7. DIMENSIONS ARE INCHES [millimeters].
8. REF-OPERATING TEMPERATURE -20°C TO 125°C.

7	2	PC22 UL1569 WHT	WIRE 22PVC UL1569 .016 7/#30
6	1	PC22 UL1569 RED	WIRE 22PVC UL1569 .016 7/#30
5	2	PC22 UL1569 GRY	WIRE 22PVC UL1569 .016 7/#30
4	1	PC22 UL1569 GRN	WIRE 22PVC UL1569 .016 7/#30
3	1	PC22 UL1569 BLK	WIRE 22PVC UL1569 .016 7/#30
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	2500	HOUSING PT6-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PT6-SS-150-7-PC22-24-24

PART NUMBER <b>2492</b>	MATERIAL NOTED
REVISION LEVEL B	PROJECTION 