


NOTES:

1. LEAK TEST: 290 PSI (UNIT CAN WITHSTAND PRESSURE BIDIRECTIONALLY), NO BUBBLES 1.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

3	38"	EE18 MIL BLK	WIRE 18EE MIL-W-16878/5 .015 7/#26
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE Technology 

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal® Cable Harnesses*
PTN12-SS-200-1-TEE18-12-24(20)

PART NUMBER **2508**

REVISION LEVEL -

PROJECTION 