



NOTES:

1. HE LEAK TEST @1 ATM. 10X10⁻⁷ CC/SEC OR LESS.
2. HYPOT 1000 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO COSMETIC SURFACE VOIDS LARGER THAN ϕ .035 [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 105 °C.
8. DIMENSIONS ARE INCHES [millimeters].

5	1	2256	HOUSING VS12L-AL
4	1	8L5N-SS NUT	NUT VS12-SS
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	12	JUDD24 WHT	WIRE 24 XLPE UL3239 5KV 19/#36
1	1	-116 VITON	O-RING -116 VITON 75
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
VS12L-AL-150-12-Judd24-24-15

PART NUMBER
2600

MATERIAL NOTED

REVISION LEVEL
C

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE \pm 0.5
X.X DECIMAL \pm 0.1 X.XX DECIMAL \pm 0.02 X.XXX DECIMAL \pm 0.005
ANGLES \pm 1 DEGREE SURFACE FINISH 128 microinch RMS