



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 20 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. VOIDS SMALLER THAN ϕ .035 ARE ACCEPTABLE.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.

4	1	THHN 12 GREEN	WIRE 12THHN GREEN
3	2	THHN 12 BLACK	WIRE 12THHN BLACK
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PTN12
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE \pm 0.5
 XX DECIMAL \pm 0.1 XXX DECIMAL \pm 0.02 XXXX DECIMAL \pm 0.005
 ANGLES \pm 1 DEGREE SURFACE FINISH 128 microinch RMS

	2751 Thundehawk Court Dayton, OH 45414-3445 U.S.A. tel (937) 890-1100 fax (937) 8905165 www.pave-technologyco.com	
	DESCRIPTION PTN12-SS-150-3-THHN12-240-240	REVISION LEVEL -
PART NUMBER 2610	PROJECTION 	