



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 20 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS SMALLER THAN  $\phi 0.035$  [.89] ARE ACCEPTABLE.
6. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $125^{\circ}\text{C}$ .
7. DIMENSIONS ARE INCHES [millimeters]..

4	2	THHN 12 BLUE	WIRE 12THHN BLUE
3	1	THHN 12 GREEN	WIRE 12THHN GREEN
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3279	HOUSING PTN8-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION PTN8-SS-150-3-THHN12-240-240	
PART NUMBER <b>2611</b>	MATERIAL NOTED REVISION LEVEL B
PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS