



- NOTES:
1. LEAK TEST: 290 PSI (20 BAR) MINIMUM, NO AIR BUBBLES, 3 MINUTES MINIMUM.
  2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
  3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
  5. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON EACH SIDE OF HOUSING.
  6. VOIDS SMALLER THAN Ø.035 [.89] ARE ACCEPTABLE ON EPOXY SURFACES.
  7. WIRE POSITIONING IS APPROXIMATE & VARIABLE.

6	A/R	PAVE-Seal 150	EPOXY BLACK
5	1	E26 ORANGE	WIRE 26E MIL-W-16878/4 7/#34
4	1	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
3	1	E12 WHITE	WIRE 12E MIL-W-16878/4 .013 19
2	1	E12 GREEN	WIRE 12E MIL-W-16878/4 .013 19
1	1	2613	HOUSING SO12C-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE #0.5  
 XX DECIMAL #0.1 XX DECIMAL #0.02 XXXX DECIMAL #0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thundehawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pave-technology.co.com

DESCRIPTION  
 SO12C-SS-150-2/2-TE12/26-1000mm-1000mm

PART NUMBER  
**2613**

REVISION  
 LEVEL B

PROJECTION