



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN φ.035 [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. DIMENSIONS ARE INCHES [millimeters].

6	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
5	1	-010 VITON	O-RING -010 VITON 75
4	1	E22 RED	WIRE 22E MIL-W-16878/4 .010 7/#30
3	1	E22 BLK	WIRE 22E MIL-W-16878/4 .010 7/#30
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0168	HOUSING SP6-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP6-E-150-2-TE22-12-12

PART NUMBER **2633**

REVISION LEVEL **B**

PROJECTION