



NOTES:

1. HE LEAK TEST @1 ATM. <1 X 10⁻⁶ CC/S.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

8	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
7	1	G22 YELLOW	WIRE 22 TEFLON GORE-WRAP 7/#30
6	1	G22 RED	WIRE 22 TEFLON GORE-WRAP 7/#30
5	1	G22 BLUE	WIRE 22 TEFLON GORE-WRAP 7/#30
4	1	G22 BLACK	WIRE 22 TEFLON GORE-WRAP 7/#30
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	-903 VITON	O-RING -903 VITON 75
1	1	2709	HOUSING SO6X-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE #0.5
 XX DECIMAL #0.1 XXX DECIMAL #0.02 XXXX DECIMAL #0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

	2751 Thundehawk Court Dayton, OH 45414-3445 U.S.A. tel (937) 890-1100 fax (937) 8905165 www.pave-technologyco.com	
	DESCRIPTION SO6-SS-150-4-G22-24-4	REVISION LEVEL A
PART NUMBER 2694	PROJECTION 	