



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. REF-OPERATING TEMPERATURE RANGE -30 TO 85 °C.

7	1	8L5N-SS NUT	NUT VS12-SS 316
6	A/R	PARKER O-LUBE	LUBRICANT BARIUM BASED
5	1	-116 VITON	O-RING -116 VITON 75
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	E12 RED	WIRE 12E MIL-W-16878/4 .013 19/#25
2	1	E12 BLACK	WIRE 12E MIL-W-16878/4 .013 19/#25
1	1	1180	HOUSING VS12L-SS 303
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
VS12L-SS-150-2-E12-36-36

PART NUMBER
2725

REVISION LEVEL -

PROJECTION