



RECOMMENDED RETAINING RING
TRUARC #5000-56 OR EQUAL

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø0.035 ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. WIRE POSITIONS ARE APPROXIMATE & VARIABLE.
8. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
9. (PARTS ARE DEFLASHED ON PARTING LINE +0.005 MAXIMUM.)

5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	2	-012 VITON	O-RING -012 VITON
3	1	TZZ18 PUR	WIRE 18TZZ XL-ETFE .016 WALL 7/#26
2	1	TZZ18 BRN	WIRE 18TZZ XL-ETFE .016 WALL 7/#26
1	1	1226 SP8L	HOUSING SP8L-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
.X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal Cable Harnesses
SP8L-E-150-2-TZZ18-4-20

PART NUMBER 2752

REVISION LEVEL A

PROJECTION