



NOTES:

- LEAK TEST: 5 BAR (75 PSI-REF) MINIMUM LEAK TEST, NO AIR BUBBLES, 1 MINUTE MINIMUM. 100% TESTED
ALSO NOTE: WILL WITHSTAND PRESSURE BIDIRECTIONALLY.
- HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE.
- ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
- WIRE POSITIONING IS APPROXIMATE & VARIABLE.
- NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN ∅0.035 [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
- DIMENSIONS ARE INCHES [MILLIMETERS].
- DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
- (PARTS ARE DEFLASHED ON PARTING LINE +0.005 MAXIMUM.)
- REF-TEMP RANGE OF USE -40° TO 150°C

7	1	TZ22 BLUE 19	WIRE 22TZ MILW22759/44A .006 19/#34
6	1	TZ22 WHITE	WIRE 22TZ MILW22759/44A .006 7/#30
5	1	TZ14 BLACK	WIRE 14TZ MIL-W-22759/32 19/27
4	1	TZ14 RED	WIRE 14TZ MIL-W-22759/32 19/27
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	2	-015 FLUROSILI	O-RING -015 FLUROSILICONE 70
1	1	1374 SP11M	HOUSING SP11M-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SP11M-E-150-2/2-TZ14/22-6-6

PART NUMBER **2832**

REVISION LEVEL -

PROJECTION