



RECOMMEND TRUARC N5000-43

- NOTES:
1. LEAK TEST: 100 PSI, NO BUBBLES 2 MINUTES MINIMUM.
 2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & DRAIN WIRE.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
 5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
 6. NO VOIDS LARGER THAN $\phi 0.035$ ARE ACCEPTABLE.

5	1	BARE COPPER #28	WIRE 28 BARE COPPER SOLID
4	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
3	1	-010 BUNA	O-RING -010 BUNA 75
2	1	CW5103	WIRE COONER CUSTOMER SUPPLIED
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal Cable Harnesses**
SP6L-E-150-1-CW5103-36-8

PART NUMBER **2857**

REVISION LEVEL **A**

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS