



NOTES:

1. HE LEAK TEST 1×10^{-6} CC/SEC @ 1500 PSI.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. REF-OPERATING TEMPERATURE -40 °C TO 140 °C.

5	1	-908 BUNA	O-RING -908 BUNA 75
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	3	E18 WHITE	WIRE 18E MIL-W-16878/4 7#26
1	1	2147	HOUSING SO12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co. 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
SO12-SS-150-3-TE18-10-10

PART NUMBER
2902

REVISION LEVEL
A

PROJECTION