



NOTES:

1. LEAK TEST: 450 PSI, NO BUBBLES 1 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN  $\phi .035$  ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. REF-PARTS ARE DEFLASHED ON PARTING LINE  $+.005$  MAXIMUM.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $150^{\circ}\text{C}$ .
9. EACH COLORED WIRE TWISTED WITH A BLACK WIRE 2 TO 4 TWISTS PER INCH, WIRES SHOWN NOT TWISTED FOR SIMPLICITY.

13	1	E26 YELLOW	WIRE 26AWG E TEFLON 7 STRAND
12	1	E26 WHITE	WIRE 26AWG E TEFLON 7 STRAND
11	1	E26 RED	WIRE 26AWG E TEFLON 7 STRAND
10	1	E26 PURPLE	WIRE 26AWG E TEFLON 7 STRAND
9	1	E26 ORANGE	WIRE 26AWG E TEFLON 7 STRAND
8	1	E26 GREEN	WIRE 26AWG E TEFLON 7 STRAND
7	1	E26 GRAY	WIRE 26AWG E TEFLON 7 STRAND
6	1	E26 BLUE	WIRE 26AWG E TEFLON 7 STRAND
5	8	E26 BLACK	WIRE 26AWG E TEFLON 7 STRAND
4	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
3	2	-015 VITON	O-RING -015 VITON 75
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1374M	HOUSING SP11M-E
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
**SP11M-E-150-8TP-TE26-72-72**

PART NUMBER  
**2923**

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES UNLESS OTHERWISE SPECIFIED PART IN INCHES.  
 DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED: NONE  $+.005$   
 .01 .XX .XXX DECIMAL  $\pm 0.005$   
 ANGLE DEGREE SURFACE FINISH MICROINCH RMS