



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM. SEAL IS BIDIRECTIONAL.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. REF-OPERATING TEMPERATURE -20 °C TO 150 °C.

ITEM	QTY	PART NUMBER	DESCRIPTION
4	A/R	PAVE-Seal 200	EPOXY BLACK
3	6	EE18 MIL WHITE	WIRE 18EE MIL-W-16878/5 .015 7/#26
2	3	EE18 MIL RED	WIRE 18EE MIL-W-16878/5 .015 7/#26
1	1	3150	HOUSING PTN12/M20-SS

**PAVE technology co.** 2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PTN12/M20-SS-200-9-TEE18-48-24

PART NUMBER  
**3110**

REVISION LEVEL  
**A**

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS