



NOTES:

1. LEAK TEST: 2700 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
5. DIMENSIONS IN INCHES [mm].

0.063 [1.6] MAXIMUM OVERFILL/UNDERFILL WIRES TO EXIT WITHIN Ø.75 [19] SPACING CONTROL NOT REQUIRED THIS SIDE

PRESSURE | ATMOSPHERE

7	A/R	PAVE-Seal 200	EPOXY BLACK
6	4	GXL20 WHITE	WIRE 20 XLPE ESB-MIL85-B
5	4	GXL20 RED	WIRE 20 XLPE ESB-MIL85-B
4	4	GXL20 BLACK	WIRE 20 XLPE ESB-MIL85-B
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	2	-020 BUNA	O-RING -020 BUNA 75
1	1	2309	HOUSING SP16-E
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

DESCRIPTION
SP16-E-200-12-GXL20-50-50cm

PART NUMBER
3152

REVISION LEVEL
A

PROJECTION