



NOTES:

1. LEAK TEST: 250 PSI, NO BUBBLES 2 MINUTES MINIMUM.
(QUALIFICATION ONLY: 20 MINUTES)
2. HYPOT 2000 VDC 100 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS SMALLER THAN $\phi .035$ [.89] ARE ACCEPTABLE.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. DIMENSIONS ARE INCHES [millimeters].
8. OPERATING TEMPERATURE RANGE -20°C TO 125°C .
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	2	XLPO12 GRAY	WIRE 12XLPO GENERAL CABLE 303480
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION PTN12-SS-150-2-XLPO12-24-24	
PART NUMBER 3351	MATERIAL NOTED REVISION LEVEL B
PROJECTION 	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS