



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES MINIMUM TIME PER TABLE.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN  $\phi$  .035 [.89] ARE NOT ACCEPTABLE.
7. REF-PRESSURE RATING IS BI-DIRECTIONAL EACH SIDE.
8. REF-OPERATING TEMPERATURE -20°C TO 150°C.
9. DIMENSIONS ARE INCHES [mm].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3363-1	120	5.5 MINUTES
3363	60	3 MINUTES
PART#	LENGTH X	TEST DURATION

6	2	TZZ18 PUR	WIRE 18TZZ XL-ETFE .015 WALL 7/#26
5	2	TZZ18 ORG	WIRE 18TZZ XL-ETFE .015 WALL 7/#26
4	1	TZZ18 BRN	WIRE 18TZZ XL-ETFE .015 WALL 7/#26
3	1	TZZ18 BLU	WIRE 18TZZ XL-ETFE .015 WALL 7/#26
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3377	HOUSING PTNL8-B
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PTNL8-B-150-6-TZZ18-X-6

PART NUMBER  
**3363**

MATERIAL NOTED

REVISION LEVEL  
 A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS