



NOTES:

1. LEAK TEST: 10,000 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN $\phi .035$ [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. REF-OPERATING TEMPERATURE -20°C TO 150°C.
7. DIMENSIONS ARE INCHES [millimeters].

7	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
6	1	-012 TEFLON	RING -012 TEFLON BACKUP SINGLE TURN
5	1	-012 VITON	O-RING -012 VITON 75
4	1	E24 BLACK	WIRE 24E MIL-W-16878/4 7/#32
3	1	E24 RED	WIRE 24E MIL-W-16878/4 7/#32
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	3432	PCB WEAR SENSOR
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION SP8HP-E-200-2-TE24-PCB-1	
PART NUMBER 3396	MATERIAL NOTED REVISION LEVEL A
PROJECTION 	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS