



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 6 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. CONTINUITY TEST  $< .21 \Omega$  WIRE END TO END.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. VOIDS LARGER THAN  $\phi .035$  [.89] ARE NOT ACCEPTABLE.
8. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $75^{\circ}\text{C}$ .
9. DIMENSIONS ARE INCHES [millimeters].

ITEM	QTY	PART NUMBER	DESCRIPTION
5	1	E22 SOLID WH/BL	WIRE 22E MIL-W-16878/4 BFA
4	1	E22 SOLID BLUE	WIRE 22E MIL-W-16878/4 BFA
3	1	LON-1P22-CMP	CABLE #22AWG 1PR STRD B C FEP
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1625	HOUSING PT16-SS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION PT16-SS-150-1TP-TX22S/ANX22-24-120	
PART NUMBER <b>3406</b>	MATERIAL NOTED
REVISION LEVEL -	PROJECTION ☉ ◻

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS