

- HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
- 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
- ALL PARTS MUST PASS ALL TESTS.
- WIRE POSITIONING IS APPROXIMATE & VARIABLE.
- NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN \emptyset .035 [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
- DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
- REF-OPERATING TEMPERATURE -20°C TO 155°C.
- REF-PARTS ARE DEFLASHED ON PARTING LINE +.005 [.13] MAXIMUM.
- 10. LABEL EACH END OF WIRES "1" "6" & "J" PER END VIEW. WIRE MARKERS TO BE WITHIN 3" OF WIRE ENDS.
- 11. DIMENSIONS ARE INCHES [millimeters]

ITEM	QTY	PART NUMBER	DESCRIPTION	3
1	1	3435	HOUSING SP26S-E	PAR
2	2	TZZ18 BRN	WIRE 18TZZ XL-ETFE .015 WALL 7/#26 BROWN	S
3	6	TZ8 WHITE	WIRE TZ8 MIL-W-22759/34 133/#29	DES
4	1	-325 VITON	O-RING -325 VITON	P
5	A/R	PAVE-Seal 200FR	EPOXY BLACK HI-TEMP FLAME RESISTANT	
6	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED	
-	A/R	BRADY WIRE MARKER	WIRE MARKER "1" - "6" & "J"	

2751 Thunderhawk Court Dayton, OH 45414-3445 .co prodombel EM tel (937) 890-1100 fax (937) 8905165 SP26S-E-200FR-6/2-TZ8/18-24-24

EQUAL. IF REMOVED FROM PORT, REPLACE O-RING.

NOTED 3413

 \bigcirc