



NOTES:

1. LEAK TEST: 1000 PSI, NO BUBBLES 10 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 M Ω 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. DIMENSION ARE INCHES [MILLIMETERS].
7. REF: TEMPERATURE RANGE OF USE: -20 TO 150°C.

5	1	KT30	CABLE T/C TYPE K 30AWG TEFLON
4	1	E24 RED	WIRE 24E MIL-W-16878/4 7/#32
3	1	E24 WHITE	WIRE 24E MIL-W-16878/4 7/#32
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	2422	HOUSING PT2-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal@ Cable Harnesses
 PT2-SS-200-2/1P-TE24/KT30-6-6

PART NUMBER
 3415

REVISION LEVEL -

PROJECTION