


NOTES:

1. LEAK TEST: 80 PSI N2, NO BUBBLES 50 SECONDS MINIMUM.
-SEAL CAPABLE OF WITHSTANDING PRESSURE FROM EITHER SIDE
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE WITH MATING CONNECTOR.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN $\phi.035$ [.89] ARE ACCEPTABLE.
7. FLASH REMOVED ON "GASKET SIDE" SURFACE OF ITEM 1.
8. CONTINUITY TEST WIRE END TO MATING CONNECTOR: <0.5 OHM.
9. REF-OPERATING TEMPERATURE RANGE -55°C TO 125°C.
10. DIMENSIONS ARE INCHES [millimeters].
11. TIGHTEN NUT 10-12 INCH LBS [1.13-1.36 Nm].

6	1	MOL# 51110-0460	CONNECTOR MALE CRIMP 4CKT #24-30
5	2	MOL# 50394-8200	CONTACT CRIMP 24-30AWG MOLEX
4	1	PC26 BLACK	WIRE 26PVC UL1007 .016 7/#34
3	1	PC26 RED	WIRE 26PVC UL1007 .016 7/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	CONXALL P5633	HOUSING NYLON + GASKET + HEX NUT
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION: PAVE-Seal® Cable Harnesses
CON610S-N-150-2-PC26-6-7.5

PART NUMBER	REVISION LEVEL
3443	D
PROJECTION	