



NOTES:

1. LEAK TEST: 1000 PSI N2, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN  $\phi .035$  [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE -20°C TO 125°C.
9. REF-PARTS ARE DEFLASHED ON PARTING LINE +.005 [.13] MAXIMUM.
10. DIMENSIONS ARE INCHES [millimeters].

10	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
9	2	-015 VITON	O-RING -015 VITON 75
8	1	E30 WHITE	WIRE 30E MIL-W-16878/4 7/#38
7	1	E30 VIOLET	WIRE 30E MIL-W-16878/4 7/#38
6	1	E30 RED	WIRE 30E MIL-W-16878/4 7/#38
5	1	E30 ORANGE	WIRE 30E MIL-W-16878/4 7/#38
4	1	E30 GRAY	WIRE 30E MIL-W-16878/4 7/#38
3	1	E30 BROWN	WIRE 30E MIL-W-16878/4 7/#38
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1374M	HOUSING SP11M-E
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
SP11M-E-150-6-TE30-36-36

PART NUMBER  
**3483**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS