



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN $\phi .035$ [.89] ARE NOT ACCEPTABLE.
7. MARK EACH WIRE WITH A UNIQUE NUMBER, USING THE SAME NUMBER ON EACH END OF THE WIRE.
8. REF-OPERATING TEMPERATURE -40°C TO 105°C .
9. DIMENSION ARE INCHES [millimeters].

6	8	BRADY WIRE MARKERS	NUMBERED 1-4
5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
4	1	-908 NITRILE	O-RING -908 NITRILE 70
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	4	PC20 1569-10BLU	WIRE 20PVC UL1569 .016 10 STRAND
1	1	3449	HOUSING SO12-AL ANODIZED TYPE II/CLASS I
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
SO12-AL-150-4-PC20-12-6

PART NUMBER
3495

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS