



INSTALLATION PORT
RECOMMEND TRUARC N5000-106

PART #	ITEM 2
3512	-020 BUNA
3512-1	-020 VITON

- NOTES:
1. LEAK TEST: 1500 PSI He 10X10⁻⁵ cc/s OR LESS.
 2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ALL PARTS MUST PASS ALL TESTS.
 5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
 6. REF - OPERATING TEMPERTURE RANGE: -25 TO 125 °C
 7. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN ϕ 0.035 ARE ACCEPTABLE ON ALL OTHER SURFACES.
 8. DIMENSIONS ARE INCHES [millimeters].

ITEM	QTY	PART NUMBER	DESCRIPTION
8	1	TZZ10 RED	WIRE TZZ10 MIL-W-22759/16-10-2
7	1	TZZ10 WHITE	WIRE TZZ10 MIL-W-22759/16-10-9
6	1	TZZ10 BLACK	WIRE TZZ10 MIL-W-22759/16-10-0
5	1	TZZ10 GREEN	WIRE TZZ10 MIL-W-22759/16-10-5
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
2	2	SEE TABLE	O-RING SEE TABLE
1	1	0913	HOUSING SP16-E

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION SP16-E-150-4-TZZ10-24-48	
PART NUMBER 3512	MATERIAL NOTED REVISION LEVEL A
PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE \pm 0.5
 X.X DECIMAL \pm 0.1 X.XX DECIMAL \pm 0.02 X.XXX DECIMAL \pm 0.005
 ANGLES \pm 1 DEGREE SURFACE FINISH 128 microinch RMS