



NOTES:

1. LEAK TEST: 800 PSI, NO BUBBLES 2 MINUTES MINIMUM. REF-PRESSURE SEAL IS BI-DIRECTIONAL.
2. HYPOT 630 VDC 500 MΩ MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE, SHIELD AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS SMALLER THAN Ø.035 [.89] ARE ACCEPTABLE.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. DIMENSIONS ARE INCHES [millimeters].
8. OPERATING TEMPERATURE RANGE -30°C TO 105°C.

3	1	PVC 3/C #20	CABLE PVC 3/C #20 BELDEN 9364 SHIELDED
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PTN12-SS-150-1-B9364-96-300

PART NUMBER	MATERIAL	NOTED
3531	REVISION LEVEL	B
	PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS