



**NOTES:**

1. HE LEAK TEST VACUUM  $10 \times 10^{-6}$  CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS SMALLER THAN  $\phi 0.035$  ARE ACCEPTABLE.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON THREAD SIDES OF HOUSING.
8. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $150^{\circ}\text{C}$ .

5	1	JT20	CABLE T/C TYPE K 24AWG TEFLON
4	1	EE14 BLACK	WIRE 14EE MIL-W-16878/5 19/#27 .017
3	1	EE14 RED	WIRE 14EE MIL-W-16878/5 19/#27 .017
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	3235-1	HOUSING PT12-SS
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PT12-SS-200-1P/2-JT20/TEE14-48-48

PART NUMBER  
**3560**

MATERIAL NOTED

REVISION LEVEL  
B

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS