



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN ϕ .035 [.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -30°C TO 90°C.
8. DIMENSIONS ARE INCHES [millimeters].

ITEM	QTY	PART NUMBER	DESCRIPTION
4	2	RHW10	WIRE #10RHW XLP STRANDED
3	2	RHW14	WIRE #14RHW XLP STRANDED
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1132	HOUSING PTN16-SS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 PTN16-SS-150-2/2-RHW10/RHW14-36-12

PART NUMBER 3665	MATERIAL NOTED	REVISION LEVEL -	PROJECTION ☉
----------------------------	-------------------	---------------------	-----------------

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS