



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø0.035 [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. WIRE POSITIONS ARE APPROXIMATE & VARIABLE.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON PRESSURE SIDE OF HOUSING.
8. (PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAXIMUM.)
9. DIMENSIONS ARE INCHES [MILLIMETERS].
10. REF-OPERATING TEMPERATURE RANGE -20 TO 80°C.

5	2	-012 NITRILE	O-RING -012 N602-70
4	1	PC26 RED	WIRE 26PVC UL1007 .016 7/#34
3	1	PC26 BLACK	WIRE 26PVC UL1007 .016 7/#34
2	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
1	A/R	PAVE-Seal 150	EPOXY BLACK
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

**PAVE technology co.**

DESCRIPTION  
SP8L-E-150-2-PC26-5-5

PART NUMBER <b>3813</b>	MATERIAL NOTED
REVISION LEVEL -	PROJECTION ☉ ◻

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS