



NOTES:

1. LEAK TEST: 3000 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS LARGER THAN  $\phi 0.035$  [0.89] ARE NOT ACCPETABLE.
6. REF-OPERATING TEMPERATURE RANGE  $-40^{\circ}\text{C}$  TO  $100^{\circ}\text{C}$ .
7. DIMENSIONS ARE INCHES [millimeters].

8	1	TZ22 GREY /32	WIRE 22 TEFZEL M22759/32 19/#34
7	1	TZ22 ORANGE /32	WIRE 22 TEFZEL M22759/32 19/#34
6	1	TZ22 BLACK /32	WIRE 22 TEFZEL M22759/32 19/#34
5	1	TZ22 RED /32	WIRE 22 TEFZEL M22759/32 19/#34
4	1	TZ22 BLUE /32	WIRE 22 TEFZEL M22759/32 19/#34
3	1	TZ22 WHITE /32	WIRE 22 TEFZEL M22759/32 19/#34
2	A/R	PAVE-SEAL 150	EPOXY BLACK
1	1	3945	HOUSING LWT9-T
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
LWT9-T-150-6-TZ22-6-24

PART NUMBER  
**3875**

MATERIAL NOTED

REVISION LEVEL  
C

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS