



NOTES:

1. HE LEAK TEST @ 1 ATM 10x10⁻⁸ CC/SEC OR LESS.
2. TEST IS PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS TEST.
4. VOIDS LARGER THAN Ø .035 [.89] ARE NOT ACCEPTABLE.
5. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
6. DIMENSIONS ARE INCHES [millimeters].
7. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

ITEM	QTY	PART NUMBER	DESCRIPTION
4	1	0185	NUT VS26-SS
3	1	-226 VITON	O-RING -226 VITON 75
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1531	HOUSING VS26-SS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
VS26-SS-150-PLUG

PART NUMBER
4022

MATERIAL
NOTED

REVISION LEVEL
 -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS