



NOTES:

1. LEAK TEST: 250 PSI, NO BUBBLES 30 SECONDS MINIMUM. QUALIFICATION ONLY: 750 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN  $\phi 0.035$  [.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -54 °C TO 150 °C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
10. DDMMYY IS DAY, MONTH (FIRST 3 LETTERS OF THE MONTH), & YEAR.

6	1	EEE14 UL1199RED	WIRE 14EE UL1199 19/#27 RED
5	1	EEE14 UL1199YLW	WIRE 14EE UL1199 19/#27 YELLOW
4	1	EEE14 UL1199GRN	WIRE 14EE UL1199 19/#27 GREEN
3	1	EEE14 UL1199BLK	WIRE 14EE UL1199 19/#27 BLACK
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	4184	HOUSING PTN8R-SS (316)
ITEM	QTY	PART NUMBER	DESCRIPTION


 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PTN8R-SS-200-4-TEEE14-12-5.5

PART NUMBER	MATERIAL	NOTED
4173	REVISION LEVEL	D
	PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS