



NOTES:

1. LEAK TEST: 80 PSI NITROGEN, NO BUBBLES 1.5 MINUTES MINIMUM.
QUALIFICATION ONLY: HELIUM LEAK TEST 10×10^{-9} CC/SEC OR LESS.
2. HYPOT 1000 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE, SHIELD AND HOUSING.
QUALIFICATION ONLY: 1050VAC .5mA MAXIMUM LEAKAGE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS SMALLER THAN $\phi 0.035$ [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

5	1	1308-BNP	HOUSING PT6-B ELECTROLESS NICKEL PLATED
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	E18 BLK	WIRE 18E MIL-W-16878/4 7/#26
2	1	E18 RED	WIRE 18E MIL-W-16878/4 7/#26
1	2	TEF2/C#26 TSP	CABLE 2/C BLK/WHT 7/34
ITEM	QTY	PART #	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
PT6-B-150-2/2SP-TE18/TE26-38-4

PART NUMBER
4346

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS