



| PART NUMBER | PART DESCRIPTION         | ITEM #1 | ITEM DESCRIPTION |
|-------------|--------------------------|---------|------------------|
| 4362        | PT12-B-150-8-TZ14-72-72  | 4206    | HOUSING PT12-B   |
| 4362-1      | PT12-SS-150-8-TZ14-72-72 | 3297    | HOUSING PT12-SS  |

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 6 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $125^{\circ}\text{C}$ .
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

| 3    | 8   | TZ14 BLK /34  | WIRE 14TZ MIL-W-22759/34-14-0 |
|------|-----|---------------|-------------------------------|
| 2    | A/R | PAVE-Seal 150 | EPOXY BLACK                   |
| 1    | 1   | SEE TABLE     | SEE TABLE                     |
| ITEM | QTY | PART NUMBER   | DESCRIPTION                   |

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

|                                         |                   |
|-----------------------------------------|-------------------|
| DESCRIPTION<br>PT12-* -150-8-TZ14-72-72 |                   |
| PART NUMBER<br><b>4362*</b>             | MATERIAL NOTED    |
| REVISION LEVEL<br>B                     | PROJECTION<br>☉ ◻ |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS