



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS SMALLER THAN  $\phi 0.035$  [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 105 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

10	2	PC18 UL1015 WHT	WIRE 18PVC UL1015 .032 16/#30
9	2	PC18 UL1015 RED	WIRE 18PVC UL1015 .032 16/#30
8	2	PC18 UL1015 GRN	WIRE 18PVC UL1015 .032 16/#30
7	2	PC18 UL1015 BLK	WIRE 18PVC UL1015 .032 16/#30
6	2	PC14 UL1015 GRN	WIRE 14PVC UL1015 .030 41/#30
5	2	PC14 UL1015 YLW	WIRE 14PVC UL1015 .030 41/#30
4	2	PC14 UL1015 RED	WIRE 14PVC UL1015 .030 41/#30
3	2	PC14 UL1015 BLK	WIRE 14PVC UL1015 .030 41/#30
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	2186	HOUSING PTNL16-B
ITEM	QTY	PART #	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PTNL16-B-150-8/8-PC14/18-12-26

PART NUMBER  
**4365**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS