



NOTES:

1. LEAK TEST: 150 PSI (10.3 BAR)N2, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ $[\ .89]$ ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 125°C .
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].

12	1	0894	NUT VS8-SS
11	1	-112 VITON	O-RING -112 VITON 75
10	1	E24 BROWN	WIRE 24E MIL-W-16878/4 7/#32
9	1	E24 BLUE	WIRE 24E MIL-W-16878/4 7/#32
8	1	E24 WHITE	WIRE 24E MIL-W-16878/4 7/#32
7	1	E24 VIOLET	WIRE 24E MIL-W-16878/4 7/#32
6	1	E24 ORANGE	WIRE 24E MIL-W-16878/4 7/#32
5	1	E24 GREEN	WIRE 24E MIL-W-16878/4 7/#32
4	1	E24 GRAY	WIRE 24E MIL-W-16878/4 7/#32
3	1	E24 BLACK	WIRE 24E MIL-W-16878/4 7/#32
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0892	HOUSING VS8-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 VS8-SS-150-8-TE24-200mm-200mm

PART NUMBER
4483

MATERIAL NOTED

REVISION LEVEL -

PROJECTION