



**NOTES:**

1. HE LEAK TEST VACUUM 10X10<sup>-7</sup> CC/SEC OR LESS.
2. ALCOHOL OR FOMBLIN YVAC 3 MAY BE USED TO LUBRICATE O-RINGS FOR VACUUM HELIUM LEAK TESTING.
3. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & COLOR POSITIONS ARE VARIABLE.
7. COSMETIC SURFACE VOIDS SMALLER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE.
8. DIMENSIONS ARE INCHES [millimeters].
9. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
11. PARTS WILL BE CLEANED & SHIPPED PER PAVE SPECIFICATION WI-Q-0133.

11	1	-015 VITON	O-RING -015 VITON 75 BROWN ONLY
10	1	ET28 WHITE	WIRE 28ET MIL-W-16878/6 7#36
9	1	ET28 VIOLET	WIRE 28ET MIL-W-16878/6 7#36
8	1	ET28 RED	WIRE 28ET MIL-W-16878/6 7#36
7	1	ET28 ORANGE	WIRE 28ET MIL-W-16878/6 7#36
6	1	ET28 GREEN	WIRE 28ET MIL-W-16878/6 7#36
5	1	ET28 BROWN	WIRE 28ET MIL-W-16878/6 7#36
4	1	ET28 BLUE	WIRE 28ET MIL-W-16878/6 7#36
3	1	ET28 BLACK	WIRE 28ET MIL-W-16878/6 7#36
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	4578	HOUSING V6-304SS
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>


 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 V6-304SS-150-8-ET28-762mm-762mm

PART NUMBER	MATERIAL	NOTED
<b>4562</b>	REVISION LEVEL	A
	PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS