


NOTES:


1. LEAK TEST: 80 PSI, NO BUBBLES 21 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST
2. HYPO T630 VDC 500 MEG OHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE
6. COSMETIC SURFACE Voids SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE
7. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BIDIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	14	EE18 MIL BLK	WIRE 18EE MIL-W-16878/5 .0157/#26
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PIN12-SS
ITEM	QTY	PARTNUMBER	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pave technology co. com

PAVE technology co.
 DESCRIPTION
 PIN12-SS-150-14-TEE18-24-480

PART NUMBER
4746

MATERIAL **NOTED**
 REVISION LEVEL -
 PROJECTION 

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS