



**NOTES:**

1. LEAK TEST: 150 PSI, NO BUBBLES 1 MINUTE MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & COLOR POSITIONS ARE VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN  $\phi 0.035$  [0.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

PAVE#	ITEM 1	ITEM 1 DESCRIPTION	PAVE DESCRIPTION
4760	3354	HOUSING PT4-B	PT4-B-150-6-TE28-18-18
4760-1	4652	HOUSING PT4-SS	PT4-SS-150-6-TE28-18-18

8	1	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
7	1	E28 RED	WIRE 28E MIL-W-16878/4 .010 7/#36
6	1	E28 ORANGE	WIRE 28E MIL-W-16878/4 .010 7/#36
5	1	E28 GREEN	WIRE 28E MIL-W-16878/4 .010 7/#36
4	1	E28 BLUE	WIRE 28E MIL-W-16878/4 .010 7/#36
3	1	E28 BLACK	WIRE 28E MIL-W-16878/4 .010 7/#36
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	SEE TABLE	SEE TABLE
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
SEE TABLE

PART NUMBER \*SEE TABLE  
**4760\***

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS