



NOTES:

1. LEAK TEST: 80PSI, NO BUBBLES, 12.5 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. CONTINUITY CHECK WIRE END TO END <0.5Ω.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -40°C TO 125°C.
9. DIMENSIONS ARE INCHES [millimeters].
10. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

8	1	8L5N-SS NUT	NUT VS12-SS
7	1	-116 VITON LT	O-RING -116 VITON 75
6	5	GXL20 WHT	WIRE 20GXL BARE COPPER 7/#28
5	5	GXL20 BLK	WIRE 20GXL BARE COPPER 7/#28
4	5	TZ20 WHT/BLUE	WIRE 20TZ M22759/44 .006 19/#32
3	5	TZ20 BLK	WIRE 20TZ M22759/44 .006 19/#32
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1180	HOUSING VS12L-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
VS12L-SS-150-10-GXL20/TZ20-20FT-5FT

PART NUMBER
4793

MATERIAL NOTED

REVISION LEVEL
A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS