



PASSTHRU ASSY

- ELECTRICAL TEST: 1 OHM MAX PIN A TO SOCKET A
- MS-5015 MATEABLE, D-RING SIDE SOCKET RECEPTACLE OTHER IS PIN CONTACT RECEPTACLE. (14S-6 INSERT)
- HELIUM LEAK RATE LESS THAN 1 X 10⁻⁵ cc/sec @ 1 atm.

FINISH: ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART. ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

ISSUE	ALTERATIONS	CHANGE NO.	DATE
LET.			



PAVE Technology Co.
Dayton, Ohio USA
Pressure and Vacuum Electronics
Custom Hermetic Connectors

TITLE: PAVEMATE® I VS14

MATERIAL: NOTED

DR BY: W.L. WOOD APPROVED BY: [Signature] DRAWN FROM: LANL

CHG BY: [Signature] DATE: 23 JUL 90 SCALE: 1=1 PART NUMBER: 0292