



NOTES:

1. HE LEAK TEST @1 ATM. 10×10^{-9} CC/S OR LESS.
2. HYPOT 3000 VDC ROD TO HOUSING 0.1 mA MAXIMUM LEAKAGE (30 M Ω MINIMUM).
3. MAXIMUM CURRENT RATING 40 AMPS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. NO VOIDS LARGER THAN $\phi 0.035$ [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 150°C.

5	4	BRASS WASHER #10	WASHER #10 BRASS
4	4	BRASS NUT #10	NUT #10-32 BRASS
3	A/R	PAVE-Seal 200HV	EPOXY BLUE
2	1	0927	ROD .188"-32 THREAD COPPER
1	1	2972	HOUSING PT4-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Mate® I Connectors
PT4-SS-200HV-1-.19CU-.94-1.62

PART NUMBER	REVISION LEVEL
0926	D
PROJECTION	