



NOTES:

1. LEAK TEST 800 PSI, THREAD SIDE 2 MINUTES MIN, NO LEAKS.
2. ELECTRICAL TEST: 630 VCD, 500 MEGOMS MIN, WIRE TO WIRE & HOUSING.
3. SHIP WITH MATING CONNECTOR, NOT SHOWN.

| ITEM | QTY | PART NUMBER | DESCRIPTION |
|------|-----|---------------|--|
| 1 | 1 | SC3102A22-23P | CONNECTOR, ALUMINUM, 8 PINS |
| 2 | 1 | WH-162-S02 | SMALLEY RETAINING RING, STEEL |
| 3 | 1 | PAVE #0189 | VS22 HOUSING, STAINLESS STEEL (MOD 1335-3) |
| 4 | 1 | -224 O-RING | -224 VITON O-RING, 70 DUROMETER |
| 5 | 1 | PAVE #0199 | VS22 JAM NUT, STAINLESS STEEL |
| 6 | A/R | PAVESEAL 200 | EPOXY, HI TEMP, BLACK |
| 7 | 1 | WH-131-S02 | SMALLEY REATINING RING |
| 8 | 8 | 12 AWG EE | TEFLON WIRE (4 COLORS BLK, RED, GRN, WHT) |

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

TITLE OR PAVE ORDER CODE

VS22S-SC3102-24 PM2

PART NUMBER

1335

PROJECTION

