



NOTES:

1. HELIUM LEAK TEST, 1×10^{-7} CC/SEC, THREAD SIDE.
2. ELECTRICAL TEST, 630 VDC, 500 MEGOHMS MIN CONTACT TO CONTACT & HOUSING.
3. ITEMS 1, 9, & 10 TO SHIP W/ASSEMBLY.

| | | | |
|------|-----|---------------------|--------------------------------|
| 10 | 2 | SC85049/38-21M | STRAIN RELIEF |
| 9 | 1 | D38999/26FG35SN | PLUG, STRAIGHT, 79 #22 SOCKETS |
| 8 | 1 | D38999/20FG35PN | RECEPT., 79 #22 PINS |
| 7 | A/R | PAVESEAL 150 | EPOXY |
| 6 | 1 | 0199 | NUT, VS22-SS |
| 5 | 1 | -224 VITON 75A | O-RING |
| 4 | 1 | 1499 | VS22-SS HOUSING |
| 3 | A/R | PAVESEAL 150 COLLAR | EPOXY |
| 2 | 1 | D38999/20FG35SN | RECEPT., 79 #22 SOCKETS |
| 1 | 1 | D38999/26FG35PN | PLUG, STRAIGHT, 79 #22 PINS |
| ITEM | QTY | ITEM NUMBER | ITEM DESCRIPTION |



DESCRIPTION
VS22-SS-150-79-22-999/20SP

PART NUMBER
1492

PROJECTION



ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS