



WIRE LENGTH TABLE

PART NUMBER	DIMENSION	
	X	Y
1557	96	48
1557-1	72	72

NOTES:

1. LEAK TEST:

1557: HE LEAK TEST @1 ATM. 10^{-7} CC/S.

1557-1: 1500 PSI N₂, NO BUBBLES 6 MINUTES MIN.

2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO SHIELD & HOUSING

3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
5	A/R	PAVE-Seal 80	EPOXY BLACK
4	1	0894	NUT VS8-SS SPIRALOCK
3	1	-112 VITON	O-RING -112 VITON 75
2	1	0892	HOUSING VS8-SS
1	145"	RG179 M17/094	WIRE COAX M17/094 B83264
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION

VS8-SS-80-1-RG179-X-Y

PART NUMBER

1557

PROJECTION

