

WIRE LENGTH TABLE


PART NUMBER	DIMENSION		
	X	Y	Z
1679	36"	180"	218"
1679-1	48"	48"	98"

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 9 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.



3	8P@Z	SEE TABLE	JT20	CABLE T/C TYPE J 20AWG TEFLON
2	A/R		PAVE-Seal 200	EPOXY BLACK
1	1		1270	HOUSING PTN12-SS
ITEM	QTY		PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
PTN12-SS-200-8P-JT20-X-Y SEE TABLE

PART NUMBER 1679	PROJECTION  
----------------------------	---