



NOTES:

1. LEAK TEST @20 PSI N2, 330 SEC MIN, NO VISIBLE BUBBLES.
2. HIPOT TEST @630VDC, 500 MEGOHMS, 10 ms MIN, WIRE TO WIRE & HOUSING

14	1	4443K683	PIPE CAP, 316 SS, THREADED, 3000LBS, 3/8"
13	1	4475K83	PIPE NIPPLE, 316 SS, SEAMLESS, SCHED 80, 3/8X8"
12	90@132	ALPHA 5856/7-10	TE20, VIOLET
11	90@132	ALPHA 5856/7-9	TE20, GRAY
10	90@132	ALPHA 5856/7-8	TE20, ORANGE
9	90@132	ALPHA 5856/7-7	TE20, BROWN
8	90@132	ALPHA 5856/7-6	TE20, BLUE
ITEM	QTY	PART #	DESCRIPTION

7	90@132	ALPHA 5856/7-5	TE20, YELLOW
6	90@132	ALPHA 5856/7-4	TE20, GREEN
5	90@132	ALPHA 5856/7-3	TE20, RED
4	90@132	ALPHA 5856/7-2	TE20, BLACK
3	90@132	ALPHA 5856/7-1	TE20, WHITE
2	A/R	PAVE-Seal 150	EPOXY
1	1	1N-ASA-11-600	NORCAL HALF NIPPLE
ITEM	QTY	PART #	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, Ohio 45416-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pave technology.com

DESCRIPTION
 ASA11-SS-150-900/1-TE20-T-60-60

PART NUMBER
1681

PROJECTION



ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 XX DECIMAL +/- .02 XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS