



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE
4. WIRE POSITIONS AND COLOR ARRANGEMENTS ARE APPROXIMATE & VARIABLE.

8	A/R	PAVE-Seal 200	EPOXY BLACK
7	3@75°	EE18 MIL BLK	WIRE 18EE MIL-W-16878/5 .015 7/#26
6	3@75°	EE18 MIL BROWN	WIRE 18EE MIL-W-16878/5 .015 7/#26
5	3@75°	EE18 MIL GRAY	WIRE 18EE MIL-W-16878/5 .015 7/#26
4	3@75°	EE18 MIL GRN	WIRE 18EE MIL-W-16878/5 .015 7/#26
3	3@75°	EE18 MIL ORANGE	WIRE 18EE MIL-W-16878/5 .015 7/#26
2	3@75°	EE18 MIL WHITE	WIRE 18EE MIL-W-16878/5 .015 7/#26
1	1	1132	HOUSING PTN16-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION

PTN16-SS-200-18-TEE18-24-48

PART NUMBER

1801

PROJECTION

