



**NOTES:**

1. LEAK TEST: 180 PSI, NO BUBBLES 1.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.

3	A/R	PAVE-Seal 200FR	EPOXY BLACK FLAME RESISTANT
2	30@37	#22CABLE	WIRE 22E CUS SUPPLIED
1	1	1625	HOUSING PT16-SS
ITEM QTY	PART#	DESCRIPTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

TITLE OR PAVE ORDER CODE  
**PT16-SS-200FR-30-#22CABLE-18-18**

PART NUMBER  
**1822**

PROJECTION

2751 Thunderhawk Court  
Dayton, Ohio 45414-3445  
U.S.A.  
(937)890-1100  
fax (937)890-5165  
www.pavetechnologyco.com